

NSN 5935-01-082-0189 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-082-0189 **Thread Class:** 2b **Thread Direction:**

Body Style: Straight shape, internal coupling **Overall Length:**

Overall Diameter:

0.312 inches

0.750 inches

Right-hand

Environmental Protection:

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

Cable Entrance Diameter:

0.085 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Frequency Rating:

18000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

36

Thread Size:

0.250 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Copper single mating end single contact grouping and gold single mating end single contact grouping

NSN 5935-01-082-0189

Electrical Plug Connector - Page 2 of 2



Insert Material: Plastic fluorocarbon single mating end **Contact Surface Treatment Specification:** Mil-c-14550 cl iv military specification 1st treatment response single mating end single contact grouping and mil-g-45204 military specification 2nd treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel comp 303 **Shell Surface Treatment:** Gold **Shell Material Specification:** Qq-s-764 cond a federal specification single material response **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact and body surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a **Unit Of Measure:** Demilitarization: No

Fiig: A039b0

Mil-std (military Standard):

Mil-c-14550 spec.