NSN 5935-01-082-0194

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-082-0194 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 1.140 inches **Overall Width:** 0.500 inches **Body Height:** 0.160 inches **Environmental Protection:** Shock resistant and thermal shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 0.980 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:**

Copper alloy single mating end single contact grouping **Contact Surface Treatment:**

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Wire wrap single mating end single contact grouping

NSN 5935-01-082-0194

Electrical Receptacle Connector - Page 2 of 2



| Unable To Decode: |
|---|
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 16 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Furnished items - mounting plate |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.016 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No Fiig: A039b0