

View Online at <https://aerobasegroup.com/nsn/5935-01-082-5140>

**Body Style:**

Straight edge type w/card guide

**Overall Length:**

4.208 inches

**Overall Width:**

0.340 inches

**Body Height:**

0.458 inches

**Environmental Protection:**

Corrosion resistant

**Board Accommodated Length:**

4.067 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**End Application:**

Tarawa class lha, emory s. Land class as, wasp class lhd, nimitz class cvn, sirius class t-afs 8, spruance class dd (963), los angeles class ssn (688), forrestal class cv, oliver perry class ffg. B-1 aircraft support equipment.

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

50 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.