Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-082-5366

## Body Style:

Straight shape, internal coupling

### **Overall Length:**

1.020 inches

## **Overall Diameter:**

1.281 inches

#### **Environmental Protection:**

Moisture proof and vibration proof

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

16-35 single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

### **Insert Position In Deg:**

30.0 and 100.0 and 128.0 and 228.0 and 265.0

#### Shell Type:

Potting

### **Connector Locking Method:**

Bayonet latch

# Connector Cable Strain Relief Method:

Potting type

#### **Operating Tempurature Rating:**

Between -65.0 degrees celsius and 175.0 degrees celsius

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

# Included Contact Quantity:

55 single mating end single contact grouping

NSN 5935-01-082-5366 Electrical Plug Connector - Page 2 of 2



#### Included Contact Type:

Round socket single mating end single contact grouping

# Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.055 gold grains, troy

Precious Material:

Gold

# **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27473 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.