

View Online at https://aerobasegroup.com/nsn/5935-01-082-7658

Thread Disection: Right-hand Overall Length: 1.250 inches Overall Diameter: 0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Thread Series Designator: Unef Shef Life: Nickel Thread Series Designator: Nickel Thread Se	
Thread Direction: Right-hand Overall Length: 1.250 inches Overall Diameter: 0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thread Jize: 0.500 inches Motorial: 0.700 inches Material: Nay acceptable Surface Treatment: Nickel Streade Steels Designator: Clange, the strap type Surface Treatment: Nickel Surface Treatment: <th>Thread Class:</th>	Thread Class:
Right-hand Overall Length: 1.250 inches Overall Diameter: 0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 1 threaded coupling Thread Vie Per Inch (tpi): 28 Otsol inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Quarterial: Nickel Thread Series Designator: Uintef Nickel Thread Series Designator: Uintef Diff Life: Nickel Thread Series Designator: Uintef Style Designator: Uintef Style Designator: Uintef Nickel Thread Series Designator: Uintef Nickel Thread Series Designator: Nickel Thread Series Designator: Uintef Nickel Thread Series Designator: Nickel Thread Series Designator: Nickel Thread Series Designator: Nickel Thread Series Designator: Nickel Thread Se	
Overall Length: 1.250 inches Overall Diameter: 0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 Size Designation: 2 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 28 Thready Qty Per Inch (tpl): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Thread Series Designator: Quartitation: Nickel Thread Series Designator: Unit of Measure: Nickel Sheft Infe: Nickel Thread Series Designator: Unit of Measure: Nickel Sheft Infe: Nickel Thread Series Designator: Unit of Measure: Nickel Sheft Infe: Nickel Sheft Infe: Nickel	
1.250 inches Overall Diameter: 0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 0.083 inches Cable Opening Quantity: 1 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Materia: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Unef Shef Life: Na Unit Of Measure: - Demilitarization: No Fig:	
Overall Diameter: 0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thread Q Up Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Surface Treatment: Nickel Unit of Measure: Nickel Dind fulse: Nickel Thread Series Designator: Unit of Measure: Na Unit of Measure: Na Dind Infanization: No Fig:	
0.551 inches Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Threaddy Quy Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Unt of Measure: Nickel Chread Series Designator: Unef Sheft Life: Na Unit of Measure: Na Surface Treatment: Na S	
Cable Opening Diameter: 0.083 inches Cable Opening Quantity: 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Style Designator: Unef Style Cores Designator: Unef Style Infe: Nickel Thread Streis Designator: Unef Style Off Measure: Prod Dirt Of Measure: Prod Prod Thread Streis Designator: Prod Dirt Of Measure: Prod Prod Streignation: Prod Streignation: Prod Streignation: <	
0.083 inches Cable Opening Quantity: 1 Cable Opening Quantity: 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thread Guaphing Thread Quy Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Catreatment: Nickel Style Designator: Clamp, tis strap type Clamp, ti	
Cable Opening Quantity: 1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Caty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Nickel Surface Treatment: Nickel Surface Treatment: Nickel Chread Series Designator: Unef Shelf Life: Na Sufface Treatment: Nickel Sufface Treatment: Nickel Surface Treatment: Nickel	
1 Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Style Designator: Other Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: Nickel Thread Series Designator: Unef Shelf Life: Nickel Thread Series Designator: Unef Shelf Life: Na Dit Of Measure: To Demilitarization: No Fig:	
Size Designation: 8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: 0.500 inches Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Unef Sheff Life: Na Clamp, tie strap type Surface Treatment: Nickel Style Designator: Unef Sheff Life: Na Clamp, tie strap type Surface Treatment: Nickel Style Designator: Nickel Style Style Designator: Nickel Style S	Cable Opening Quantity:
8 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Stafface Treatment: Nickel Surface Treatment: Nickel Surface Treatment: Nickel Stafface Treatment: Nickel Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: Nickel Thread Series Designator: Unef Shelf Life: Nickel Thread Series Designator: Unef Shelf Life: Nickel The Component	
Nounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Stuffee Treatment: Nickel Stuffee Treatment: Nickel Stuffee Treatment: Nickel Stuffee Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Penilitarization: No Fig:	
1 threade coupling Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Not acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Style Designator: Other Nickel Thread Series Designator: Unef Shelf Life: N/a Designator: Unef Dint Of Measure: Demilitarization: No Fig:	
Thready Qty Per Inch (tpi): 28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Style Designator: Other Strap type Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	
28 Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unef Shelf Life: N/a Dit Of Measure: Demilitarization: No Fig:	
Thread Size: 0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Sturface Treatment: Nickel Sturface Treatment: Nickel Sturface Treatment: Nickel Durface Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.500 inches Material: Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	
Material:Any acceptableSurface Treatment:NickelStyle Designator:Clamp, tie strap typeSurface Treatment:NickelTread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Any acceptable Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	
Surface Treatment: Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Nickel Unef Shelf Life: N/a Unef Dint Of Measure: Demilitarization: No	Material:
Nickel Style Designator: Clamp, tie strap type Surface Treatment: Nickel Nickel Unef Shelf Life: N/a Untof Measure: Pemilitarization: No	
Style Designator:Clamp, tie strap typeSurface Treatment:NickelThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	
Clamp, tie strap type Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Nickel
Surface Treatment: Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Pemilitarization: No	
Nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	
A10100	
	A10100