NSN 5935-01-083-0824

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5935-01-063-0624
Body Style:
Straight type
Overall Length:
2.850 inches
Overall Height:
0.625 inches
Overall Width:
0.250 inches
Distance Between Mounting Facility Centers:
2.650 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, grade c, class 1 military specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment
response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response or qq-b-626 federal specification single material response single material response single material response or qq-b-626 federal specification single spe
contact grouping
Included Contact Quantity:
50 single mating end single contact grouping

Precious Material And Location:

Round pin single mating end single contact grouping

Contact surfaces gold

Included Contact Type:

Precious Material And Weight:

0.050 gold grains, troy

NSN 5935-01-083-0824

Electrical Receptacle Connector - Page 2 of 2



Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization:
Demilitarization: No

Mil-std (military Standard): Mil-g-45204 spec.