

View Online at <https://aerobasegroup.com/nsn/5935-01-083-0825>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, flush mount

Overall Length:

1.880 inches

Overall Height:

1.170 inches

Overall Width:

4.325 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.558 inches and 0.566 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.871 inches and 3.879 inches

Distance From Mounting Shoulder To Front Face:

Between 0.615 inches and 0.630 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

71c15 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

500.0 single mating end all contact groupings

Polarization Method:

Mating end

Shell Type:

Solid

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 grade b, class 3 or 4 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

56 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.071 gold grains, troy and 0.071 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-83733 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-83733/5 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.