NSN 5935-01-083-2354

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-083-2354 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 4.035 inches **Overall Diameter:** 1.588 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Cable Entrance Diameter:** Between 0.445 inches and 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-19 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 280.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Thready Qty Per Inch (tpi):

Cable clamp 18 **Thread Size:** 1.375 inches

NSN 5935-01-083-2354Electrical Plug Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification all treatment responses
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0