Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-083-2355



Thread Class: 2b **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 4.880 inches **Overall Diameter:** 1.968 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Cable Entrance Diameter:** Between 0.611 inches and 0.938 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28-15 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

280.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

18

Thread Size:

1.750 inches

NSN 5935-01-083-2355

Electrical Plug Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and nickel **Shell Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Included Contact Quantity:** 35 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.035 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0