NSN 5935-01-083-2366

Electrical Receptacle Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-083-2366 | |
|---|--|
| Thread Class: | |
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape | |
| Overall Height: | |
| 3.938 inches | |
| Overall Width: | |
| 3.375 inches | |
| Environmental Protection: | |
| Vibration resistant | |
| Unthreaded Mounting Hole Diameter: | |
| 0.156 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| 3.250 inches | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | |
| 2.875 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 2 | |
| Contact Position Arrangement Style: | |
| 81 all mating ends | |
| Polarization Method: | |
| Jackscrew | |
| Shell Type: | |
| Solid | |
| Connector Locking Method: | |
| Jackscrew-socket | |
| Thready Qty Per Inch (tpi): | |
| 24 | |
| Thread Size: | |
| 0.190 inches | |
| Insert Material: | |
| Plastic diallyl phthalate all mating ends | |
| Shell Material: | |
| Aluminum | |
| Shell Surface Treatment: | |
| Cadmium | |
| | |

Insert Material Specification:

Mil-m-14, sdg-f military specification single material response all mating ends

NSN 5935-01-083-2366

Electrical Receptacle Connector Body - Page 2 of 2



| Thread Series Designator: |
|------------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-m-14 spec.