

View Online at https://aerobasegroup.com/nsn/5935-01-083-2368

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Height:
3.938 inches
Overall Width:
3.375 inches
Environmental Protection:
Vibration resistant
Unthreaded Mounting Hole Diameter:
0.156 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
3.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.875 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
2
Contact Position Arrangement Style:
81 all mating ends
Polarization Method:
Jackscrew
Jackscrew Shell Type:
Shell Type:
Shell Type: Solid
Shell Type: Solid Connector Locking Method:
Shell Type:         Solid         Connector Locking Method:         Jackscrew-socket
Shell Type:         Solid         Connector Locking Method:         Jackscrew-socket         Thready Qty Per Inch (tpi):
Shell Type:         Solid         Connector Locking Method:         Jackscrew-socket         Thready Qty Per Inch (tpi):         24
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:   Plastic diallyl phthalate single mating end
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:   Plastic diallyl phthalate single mating end   Shell Material:
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:   Plastic diallyl phthalate single mating end   Shell Material:   Aluminum
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:   Plastic diallyl phthalate single mating end   Shell Material:   Aluminum   Shell Surface Treatment:   Cadmium
Shell Type:   Solid   Connector Locking Method:   Jackscrew-socket   Thready Qty Per Inch (tpi):   24   Thread Size:   0.190 inches   Insert Material:   Plastic diallyl phthalate single mating end   Shell Material:   Aluminum   Shell Surface Treatment:



**Thread Series Designator:** 

Unc

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-m-14 spec.