

View Online at <https://aerobasegroup.com/nsn/5935-01-083-5568>

**Body Style:**

Straight shape, external coupling strain relief

**Overall Height:**

2.244 inches

**Overall Width:**

2.244 inches

**Environmental Protection:**

Fuel resistant and shock resistant and vibration resistant and waterproof

**Unthreaded Mounting Hole Diameter:**

Between 0.169 inches and 0.177 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.752 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.752 inches

**Distance From Mounting Shoulder To Front Face:**

0.878 inches

**Mating End Quantity:**

1

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet shell

**Connector Cable Strain Relief Method:**

Compression nut

**End Application:**

2350-01-087-1095 tank, combat, full tracked. Tank, combat, ft, 120mm gun (m1a1), tank, abrams m-1

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Criticality Code Justification:**

Feat

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Stainless steel

**Included Contact Quantity:**

55 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.055 silver grains, troy

**Precious Material:**

Silver

**Specification Data:**

19207-12287272 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0