## NSN 5935-01-083-6918

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-083-6918 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 3.350 inches **Overall Height:** 0.485 inches **Overall Width:** 0.250 inches **Environmental Protection:** Cold resistant and heat resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 3.100 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

# NSN 5935-01-083-6918

Electrical Receptacle Connector - Page 2 of 2



Insert	Mate	ria	ŀ
mseri	iviale	शाव	ı.

Plastic diallyl phthalate single mating end or plastic phenolic single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, ty z cl 1 grade c military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

50 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-female and location-right handandjackscrew type-male and location-left hand

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.050 gold grains, troy

#### **Precious Material:**

Gold

## **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.