Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-083-7240

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.594 inches
Overall Diameter:
0.250 inches
Environmental Protection:
Vibration resistant and shock resistant and thermal shock resistant and corrosion resistant and moisture resistant
Distance From Mounting Shoulder To Front Face:
0.426 inches
Mounting Facility Thickness:
0.093 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type: Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 2, grade c military specification single treatment response single mating end single contact grouping



Terminal Type	
	le mating end single contact grouping
	ial Specification:
Qq-c-530, 1/2 h	hard federal specification single material response single mating end single contact grouping
Shell Material:	
Steel comp 303	8
Shell Material	Specification:
Qq-s-764, cond	a federal specification single material response
Insert Material	Specification:
Mil-p-19468 mil	itary specification single material response single mating end
Included Cont	act Quantity:
1 single mating	end single contact grouping
Bushing Acco	mmodation Hole Shape:
Round w/flat	
Included Conta	act Type:
Coaxial pin sinç	gle mating end single contact grouping
Precious Mate	rial And Location:
Contact surface	es gold
Precious Mate	rial And Weight:
0.005 gold graiı	ns, troy
Precious Mate	rial:
Gold	
Thread Series	Designator:
Uns	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	n:
No	
Fiig:	
A039b0	
Mil-std (militar	y Standard):
Mil-g-45204 spe	ec.