

View Online at <https://aerobasegroup.com/nsn/5935-01-084-0791>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/cable clamp

Overall Length:

1.406 inches

Overall Height:

Between 0.985 inches and 1.015 inches

Overall Width:

Between 0.985 inches and 1.015 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and weatherproof

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.713 inches and 0.723 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.713 inches and 0.723 inches

Cable Entrance Diameter:

0.151 inches

Distance From Mounting Shoulder To Front Face:

Between 0.640 inches and 0.671 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping or silver single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping or qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, cond h, ht federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Surface Treatment Specification:

Qq-s-365 federal specification single treatment response

Shell Material Specification:

Qq-b-626, alloy 360, 1/2 hard federal specification single material response

Insert Material Specification:

Lp-403 federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact and body surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.