NSN 5935-01-084-2440

Thread Class:

Stainless steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-084-2440

2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.375 inches
Overall Height:
1.250 inches
Overall Width:
1.250 inches
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
Between 0.708 inches and 0.728 inches
Threaded Device Type:
Coupling facility and back shell
Mating End Quantity:
1
Polarization Method:
Keyway or multiple keyway
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18 and 36
Thread Size:
1.062 inches and 0.930 inches
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Rhodium single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Mil-c-26636 military specification single treatment response single mating end single contact grouping
Shell Material:

NSN 5935-01-084-2440

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Mil-std-171 military standard single treatment response
Shell Material Specification:
Mil-s-862 military specification single material response
Precious Material:
Rhodium
Thread Series Designator:
Unef and uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-c-26636 spec.