

View Online at <https://aerobasegroup.com/nsn/5935-01-084-5779>

Body Style:

Right angle type

Overall Length:

5.540 inches

Overall Height:

0.580 inches

Overall Width:

0.286 inches

Environmental Protection:

Salt water resistant and vibration resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.097 inches

Distance Between Mounting Facility Centers:

5.340 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Shell Type:

Solid

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Tapered pin single mating end single contact grouping

Contact Material Specification:

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin right-hand at 7 o'clock

Shell Material:

Aluminum alloy 6063

Shell Surface Treatment:

Anodize

Shell Material Specification:

Qq-a-200/9b federal specification single material response

Insert Material Specification:

Mil-p-20693, type 1 military specification single material response single mating end

Included Contact Quantity:

100 single mating end single contact grouping

Included Contact Type:

Flat pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.100 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.