# NSN 5935-01-084-7282

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-084-7282

## **Body Style:**

Straight shape w/screw locks

## **Overall Length:**

2.850 inches

## **Overall Height:**

0.915 inches

## **Overall Width:**

0.250 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and corrosion resistant and humidity resistant and thermal shock resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Connector Locking Method:**

Friction or jackscrew-socket

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

## **Included Contact Quantity:**

50 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

Electrical Plug Connector - Page 2 of 2



**Precious Material And Weight:** 

0.050 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.