

View Online at <https://aerobasegroup.com/nsn/5935-01-084-9206>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

T-shape

Overall Length:

0.325 inches

Overall Height:

1.790 inches

Overall Width:

0.286 inches

Environmental Protection:

Shock resistant and vibration resistant and hermetic and humidity resistant

Mounting Facility Thickness:

0.218 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

20

Thread Size:

0.750 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and nickel all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification 1st treatment response all mating ends single contact grouping and qq-n-290, cl 2, type 7 federal specification 2nd treatment response all mating ends single contact grouping

Contact Material Specification:

Qq-b-626, comp 22, 1/2 hard federal specification single material response all mating ends single contact grouping

Shell Material:

Copper alloy and steel

Shell Surface Treatment:

Gold and nickel

Shell Surface Treatment Specification:

Qq-n-290, cl 2, type 7 federal specification 2nd treatment response

Shell Material Specification:

Qq-b 626 federal specification single material response or qq-s-633 federal specification single material response

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contacts and shell surfaces gold

Precious Material And Weight:

0.115 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.