

View Online at <https://aerobasegroup.com/nsn/5935-01-084-9214>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.465 inches

Overall Height:

1.453 inches

Overall Width:

1.453 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.156 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.156 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

20-16 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

238.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thread Length:

0.290 inches

Thready Qty Per Inch (tpi):

18

Thread Size:

1.188 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, class 3, grade b military specification single treatment response

Shell Material Specification:

Qq-a-367, 6061-t6 federal specification single material response

Included Contact Quantity:

16 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.016 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms3470 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0