

View Online at <https://aerobasegroup.com/nsn/5935-01-085-0035>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

Between 0.858 inches and 0.918 inches

**Overall Diameter:**

1.380 inches

**Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and vibration proof

**Distance From Mounting Shoulder To Front Face:**

Between 0.761 inches and 0.781 inches

**Mounting Facility Thickness:**

0.125 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

12-dec single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Key, multiple key groove

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.938 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Metal ferrous single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Glass single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Steel

**Shell Surface Treatment:**

Tin

**Included Contact Quantity:**

12 single mating end single contact grouping

**Bushing Accommodation Hole Shape:**

Round w/flat

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.012 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unef

**Specification Data:**

81349-mil-c-83723/81 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.