

View Online at <https://aerobasegroup.com/nsn/5935-01-085-0466>

Overall Length:

4.000 inches

Overall Height:

0.830 inches

Overall Width:

0.280 inches

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

3.0 1st mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

300.0 1st mating end all contact groupings

Polarization Method:

Guide pin/socket

End Application:

TEST-SE-T,F-IREC

Terminal Location:

Back 2nd mating end single contact grouping

Contact Material:

Copper alloy 1st mating end all contact groupings

Contact Surface Treatment:

Gold 1st mating end all contact groupings and nickel 1st mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1 military specification 1st treatment response 1st mating end all contact groupings and qq-n-290 federal specification 2nd treatment response 1st mating end all contact groupings

Terminal Type:

Pin 2nd mating end single contact grouping

Contact Material Specification:

Qq-b-626, 1/2 or 3/4 hard federal specification single material response 1st mating end all contact groupings

Guide Design And Location:

D shape pin right-hand bottom at 11 oclock

Included Contact Type:

Curved pin 1st mating end all contact groupings

Precious Material And Location:

Contacts gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.