Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-085-3917

# Body Style:

Straight shape

# **Overall Length:**

Between 1.335 inches and 1.435 inches

## **Overall Width:**

Between 0.245 inches and 0.255 inches

#### **Environmental Protection:**

Thermal shock resistant and moisture resistant and vibration resistant and shock resistant and corrosion resistant

### Distance Between Mounting Facility Centers:

Between 1.210 inches and 1.220 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

51 single mating end

**Terminal Location:** 

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Copper single mating end single contact grouping and gold single mating end single contact grouping

## **Contact Surface Treatment Specification:**

Mil-g-45204, type ii military specification 1st treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### **Included Contact Quantity:**

51 single mating end single contact grouping

### Included Contact Type:

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surf gold

### **Precious Material:**

Gold

Shelf Life:

N/a

# Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.