Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-085-6254

Body Style:

Angle shape

**Overall Length:** 

2.540 inches

## **Overall Height:**

1.250 inches

#### **Overall Width:**

0.275 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

300.0 single mating end single contact grouping

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Wire wrap single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

25 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.025 gold grains, troy

# NSN 5935-01-085-6254

Electrical Plug Connector - Page 2 of 2

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.

