

View Online at <https://aerobasegroup.com/nsn/5935-01-085-6467>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

2.835 inches

Overall Height:

2.937 inches

Overall Width:

1.660 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Cable Entrance Diameter:

1.110 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

25-104 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Jackscrew and shell

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Thread Length:

0.320 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 1 federal specification single treatment response

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Shell Guide Type And Location Designator:

E slot

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.104 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-std-15000