## NSN 5935-01-085-6512

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-085-6512 **Body Style:** Straight shape **Overall Length:** 2.175 inches **Overall Height:** 0.680 inches **Overall Width:** 0.610 inches **Environmental Protection:** Corrosion resistant and moisture proof and shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.180 inches **Distance Between Mounting Facility Centers:** Between 1.832 inches and 1.852 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Cadmium single mating end single contact grouping and copper single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** 

Steel

**Shell Surface Treatment:** 

Chromate and zinc

## NSN 5935-01-085-6512

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:** 

24 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.024 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.