

View Online at <https://aerobasegroup.com/nsn/5935-01-085-9061>

Body Style:

Right angle type

Overall Length:

3.200 inches

Body Width:

0.312 inches

Body Height:

0.350 inches

Environmental Protection:

Corrosion resistant

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

2.800 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1100.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1550.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Side single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-c-8384 military specification single treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

2 guide pins

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-8384 spec.