

View Online at <https://aerobasegroup.com/nsn/5935-01-085-9066>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Diameter:

0.187 inches

Environmental Protection:

Corrosion resistant and shock resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.264 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

40

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic fluorocarbon single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, class 4 military specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Material Specification:

Qq-b-626, 1/2 hard, alloy 360 federal specification single material response

Insert Material Specification:

L-p-403 federal specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.101 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.