## NSN 5935-01-086-5524

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-086-5524 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 2.685 inches **Environmental Protection:** Moisture resistant and shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 2.352 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Glass single mating end and plastic polyester single mating end **Terminal Type:** Crimp single mating end single contact grouping **Included Contact Quantity:** 36 single mating end single contact grouping

**Included Contact Type:** 

Leaf spring single mating end single contact grouping

## NSN 5935-01-086-5524

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0