

View Online at <https://aerobasegroup.com/nsn/5935-01-086-7278>

Body Style:

Straight shape

Overall Length:

Between 1.142 inches and 1.162 inches

Overall Height:

Between 0.343 inches and 0.353 inches

Overall Width:

Between 0.238 inches and 0.258 inches

Unable To Decode:

Unable to decode and unable to decode

Unable To Decode:

Unable to decode and unable to decode

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

Between 1.042 inches and 1.053 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

51 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Shell Type:

Potting

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1, grade c military specification single treatment response single mating end single contact grouping

Shell Material:

Plastic polyamide

Shell Material Specification:

Mil-m-19887 military specification single material response

Insert Material Specification:

Mil-m-19887 military specification single material response single mating end

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.