## NSN 5935-01-087-1990

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-087-1990 **Thread Class:** 2a and 2b and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Rectangular shape Center To Center Distance Between Mounting Facilities Parallel To Length: 2.703 inches **Overall Width:** 1.328 inches **Environmental Protection:** Moisture proof and salt water resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.469 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 34 single mating end **Polarization Method:** Jackscrew and shell Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 and 40 **Thread Size:** 0.138 inches and 0.112 inches **Insert Material:** Plastic diallyl phthalate single mating end **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Insert Material Specification:** Mil-m-14 ty sdg-f military specification single material response single mating end

C slot

**Shell Guide Type And Location Designator:** 

## NSN 5935-01-087-1990

Electrical Receptacle Connector Body - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Special Features:
Items furnished as accessories -mounting plate
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.