

View Online at https://aerobasegroup.com/nsn/5935-01-087-8445

Thread Dissi 2a and 2b Thread Direction: Left-hand and right-hand Body Style: Straight shape, internal coupling Overall Length: 1.800 incles Overall Diameter: 2.315 incles Environmental Protection: Waterpool Thread Davied Type: Back shell and coupling facility Back shell and coupling facility Statistic Mathematic 2.45 incles Posticat Dosition Arrangement Style: 3.24 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 3.0 Stell Type: Solid Concert tocking Method: Insertally threaded coupling ring Thread Dive Fractmente: 1.75 inches and 2.000 inches Shell Strates: 1.75 inches and 2.000 inches Shell Strates: 1.76 inches and 2.000 inches Shell Strates: 1.75 inches and 2.000 inches Shell Strates: Shell Strate Testmente:	
Tread Interction: Luch-hand and right-hand Body tyle: Straight shape, internal coupling Overal Langth: 1.860 Inches Overal Diameter: 2.315 Inches Environmental Protection: Vaterproof Treade Device Type: Back shell and coupling facility Mating End Quantity: 1 Concer Dosition Arrangement Style: 32-8 single maine and Polarization Method: Kayay or multiple kayway Instrement Desc Solid Concer Locking Method: Solid Concer Locking Method: Internally threaded coupling ing Thread Size: 1.375 Inches and 2.000 Inches Shell Type: 2.164 and 10 Thread Size: 1.375 Inches and 2.000 Inches Shell Market Treating Incoments Shell Market Treate	Thread Class:
Lethand and right-hand Brody Style: Straigt shape, internal coupling Overall Langth: 1.800 Inches Chrontental Protection: 2.315 Inches Environmental Protection: Value prof Thraded Device Type: Back shell and coupling facility Mating End Quantity: 1 Concar Position Arrangement Style: 32-8 single mating end Polarization Method: Kayway or multiple keyway Batel Type: Sold Polarization Method: Round Coupling facility Sold Polarization Method: Isser Position In Deg: Out Sold Polarization Method: Isser Position In Deg: Sold Polarization Method: <t< td=""><td>2a and 2b</td></t<>	2a and 2b
Brody Style: Straight shape, internal coupling Overal Length: 1.860 Inches Overal Jönneter: 2.315 Inches Environmental Protection: Waterpool Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Polarization Arrangement Style: 32-8 single mating end Polarization National Keyway or multiple keyway Polarization Natode: Konge Value Sold Connector Locking Method: Internally threaded coupling ring Thready Qy Per Inch (tp): 1/35 linches and 2.000 linches Stell Trace Stell Stell Strafee Treatment: 1.75 linches and 2.000 linches Stell Strafee Treatment: 1.76 Stelderal specification 1st material response or qq-s-764 federal specification 2nd material response Stell Strafee Treatment: 1.76 Stelderal specification 1st material response or qq-s-764 federal specification 2nd material response 1.76 Stelderal specification 1st material response or qq-s-764 federal specification 2nd material response 1.76 Stelderal specification 1st materi	Thread Direction:
Straight shape, internal coupling Overal Length: 1.80 inches Overal Diameter: 2.315 inches Environmental Protection: Waterproof Threade Device Type: Back shell and coupling faolitity Maine Fao Quantity: 1 Context Position Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keyway Rose or multiple keymay 0 Shall Shall 10 Shall 11 12 Context Position Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keymay Board Context Locking Method: Shall Shall Thread Sta: 1.1 Shall stariation 1.2 Shell Metariation Shell Staries Shell Metariation Specification 1st material response or qq-s-764 federal specification 2nd material response Shell Methote:	Left-hand and right-hand
Overall Length: 1.860 inches Overall Diameter: 2.315 inches Environmental Protection: Vaterprof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 32-8 single maing end Polarization Method: Kayway or multiple kayway Insert Position In Deg: 0-0 Shell Type: Solid Concector Locking Method: Internality threaded coupling ring Threaded coupling ring Threaded coupling ring Threaded Size: 1.85 inches and 2.000 inches Shell Material: Steel comp 302 or steel comp 303 Shell Material: Passivate Qae-785 federal specification 1st material response or qq-s-784 federal specification 2rd material response Thread Size Duand double stub Shell Line: Na	Body Style:
1.880 inches 2.315 inches 2.315 inches Environmental Protection: Vaterproof Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 23-8 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0-0 Shell Type: Solid Connector Locking Method: Insert Position In Deg: 0-0 Shell Type: Solid Connector Locking Method: Insert Position In Deg: 10-0 Shell Type: Solid Connector Locking Method: Instended coupling ring Thread Stace: 1.375 inches and 2.000 inches Shell Surface: 1.375 inches and 2.000 inches Shell Surface: 1.375 inches and 2.000 inches Shell Surface: 2.384 Shell Surface: 2.395 dederal specification 1st material response or	Straight shape, internal coupling
Overall Diameter:2.315 inchesEnvironmental Protection:WaterpoofThreaded Device Type:Back shell and coupling facilityMatting End Quantity:1Contact Position Arrangement Style:32-8 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Dog:0.0Shell Type:SoldContect Locking Method:Interrally threaded coupling ringThready Oty Per Inch (pt):16 and 10Thread State:17.15 inches and 2.000 inchesShell MaterialState Ing State I comp 303Shell MaterialState I comp 304 or statel comp 303Shell Material Specification 1 st material response or quis-764 federal specification 2nd material responseIn and double stubChread StateIn and use tubeState I constate I st material response or quis-764 federal specification 2nd material responseIn and double stubState I constate I st material response or quis-764 federal specification 2nd material responseIn and double stubState I constate I c	Overall Length:
2.315 inches Exvironmental Protection: Vaterproof Treaded Device Type: Backshell and couping facility: Mating End Quantity: Mating End Quantity: Mating End Quantity: Mating End Quantity: Contact Position Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keyway Arrent Position In Dag: Volarization Method: Keyway or multiple keyway Nove Position In Dag: Volarization Method: Nove Position In Dag: Volarization Position In Company Position Pos	1.860 inches
Everomental Protection: Waterproof Treaded Device Type: Back shall and coupling facility Mating End Quantity: 1 Contact Desition Arrangement Style: 32-8 single mating and Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Contact Locking Method: Internality threaded coupling ring Thready Day P Inch (pi): 1 diard 1 Shell Material: Stell comp 302 or steel comp 303 Shell Material Passivate Passivate Chard Steel Diday Shell Age/Cification 1st material response or qu-s-764 federal specification 2nd material response Thread Steit Chard Steit Eusignation: Chard Steit Eusignation: Diday Shell Material Specification 1st material response or qu-s-764 federal specification 2nd material response Thread Steit Eusignation: Diday Shell Steit Eusignation: Diday Steit Steit Eusignation: Diday Steit St	Overall Diameter:
Waterprod Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Charled Notation Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Concotor Locking Method: Internally threaded coupling ring Thready Quy Per Inch (tpi): 16 and 10 Thread State: 1.875 inches and 2.000 inches Shell State: 1.875 inches and 2.000 inches Shell Surface Treatment: Pasivate Pasivate Pasivate Shell Material Specification 1st material response or qq-s-764 federal specification 2nd material response In and double stub Shell Lite: Ival	2.315 inches
Threaded Device Type: Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Interaded coupling ring Thready Of Por Inch (tpi): 16 and 10 Thread State: 175 Sinches and 2.000 inches Shell Material: Stele comp 302 or stele comp 303 Shell Surface Treatment: Passivale Shell Material Specification 1st material response or qq-s-764 federal specification 2nd material response Thread Steise In and double stub	Environmental Protection:
Back shell and coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 32-8 single mating end Polarization Method: Reyway or multiple keyway Insert Position In Deg: 0.0 Shell Contact Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 16 and 10 Thread Size: 1.875 inches and 2.000 inches Shell Material: Restore Treatment: Passivate Shell Material Quarter Treatment: Passivate Shell Material Specification 1st material response or qq-s-764 federal specification 2nd material response Taread Subje stub Shell Austrial specification 1st material response or qq-s-764 federal specification 2nd material response Thread Subje stub Shell Keitie: In and double stub	Waterproof
Mating End Quantity: 1 Contact Position Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 16 and 10 Thread Size: 1.875 inches and 2.000 inches Shell Material: Stel Compactor Foretherene Passivate Shell Material Specification 1st material response or qq-s-764 federal specification 2nd material response Chardes stub Shell Life: Iva	Threaded Device Type:
1 Contact Position Arrangement Style: 32-8 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 16 and 10 Thread Size: 1.875 inches and 2.000 inches Shell Material: Stel comp 302 or steel comp 303 Shell Material: Parsystate Qrs-r68 federal specification 1st material response or qq-s-r64 federal specification 2nd material response Thread Streis Un and double stub Shelf Life: Nat	Back shell and coupling facility
Contact Position Arrangement Style:32-8 single mating endPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Stell comp 303Shell Material:Questrated coupling stell comp 303Shell Material Specification 1st material response or ques-764 federal specification 2nd material responseFraced Series Designator:Un and double stubShell Life:NatiShell Life:National StudeStell Life:National Stell Life:National Stell Life:National Stell	Mating End Quantity:
32-8 single mating end Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Thready Qty Per Inch (tpi): 16 and 10 Thread Size: 1.875 inches and 2.000 inches Shell Material: Steel comp 302 or steel comp 303 Shell Surface Treatment: Passivate Alers-F63 federal specification 1st material response or qq-s-764 federal specification 2nd material response Thread Sue Subjectification In and double stub Shell Life: Iva	1
Plariation Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateAnd Material Specification 1st material response or qq-s-764 federal specification 2nd material responseIn and double stubShell Life:IvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIvaIva	Contact Position Arrangement Style:
Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):16 and 10Thread Size:17.57 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateGuers To Size:17.62 Size:18.61 Surface Treatment:PassivateDel Surface Treatment:In and double stubHurenal Specification 1st material response or qq-s-764 federal specification 2nd material response.Firead Series Designator:In and double stubShell Life:In and double stubShell Life:In and stubShell Life:In and Surface Thread Series Designator:In and Surface Series Designator:In an double stubSurface Series Designator:In an double stubSurface Series Designator:In an double stubIn an and Surface Series Designator:In an and Series Designator: </td <td>32-8 single mating end</td>	32-8 single mating end
Insert Position In Deg:0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateGuers Affectivation 1st material response or qq-s-764 federal specification 2nd material responseFuread Series Designator:Un and double stubShell Life:NatNatShell Life:NatNatShell Life:NatShell Surface Series Designator:Shell Life:Shell Life:<	Polarization Method:
0.0Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Cty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateGar-s63 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShell Life:Na	Keyway or multiple keyway
Shell Type:SolidConnector Locking Method:Internally threaded coupling ringThready Cty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material specification 1st material response or qq-s-764 federal specification 2nd material responseThread Size:In and double stubShell Life:Na	Insert Position In Deg:
SolidConnector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:Nat	0.0
Connector Locking Method:Internally threaded coupling ringThready Qty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread SettiesUn and double stubShell Life:N/a	Shell Type:
Internally threaded coupling ring Inteready Qty Per Inch (tpi): 16 and 10 Incread Size: 1.875 inches and 2.000 inches Shell Material: Steel comp 302 or steel comp 303 Shell Surface Treatment: Passivate Shell Material Specification Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Incread Series Designator: Un and double stub Shelf Life: N/a	Solid
Thready Qty Per Inch (tpi):16 and 10Thread Size:1.875 inches and 2.000 inchesShell Surface Inch (tpi):Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:N/a	Connector Locking Method:
16 and 10Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:N/a	Internally threaded coupling ring
Thread Size:1.875 inches and 2.000 inchesShell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:N/a	Thready Qty Per Inch (tpi):
1.875 inches and 2.000 inches Shell Material: Steel comp 302 or steel comp 303 Shell Surface Treatment: Passivate Shell Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Thread Series Designator: Un and double stub Shelf Life: N/a	16 and 10
Shell Material:Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:N/a	Thread Size:
Steel comp 302 or steel comp 303Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:N/a	1.875 inches and 2.000 inches
Shell Surface Treatment:PassivateShell Material Specification:Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material responseThread Series Designator:Un and double stubShelf Life:N/a	Shell Material:
Passivate Shell Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Thread Series Designator: Un and double stub Shelf Life: N/a	
Shell Material Specification: Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Thread Series Designator: Un and double stub Shelf Life: N/a	Shell Surface Treatment:
Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response Thread Series Designator: Un and double stub Shelf Life: N/a	Passivate
Thread Series Designator: Un and double stub Shelf Life: N/a	Shell Material Specification:
Un and double stub Shelf Life: N/a	Qq-s-763 federal specification 1st material response or qq-s-764 federal specification 2nd material response
Shelf Life: N/a	Thread Series Designator:
N/a	Un and double stub
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

Electrical Plug Connector Body - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0