NSN 5935-01-087-9214

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-087-9214

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
2.189 inches
Overall Diameter:
2.209 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
32-6 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
135.0 single mating end 1st contact grouping41.0 single mating end 2nd contact grouping73.0 single mating end 3rd contact grouping22.0
single mating end 4th contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.750 inches and 2.000 inches
Terminal Location:
Back single mating end all contact groupings
Contact Material:

Contact Surface Treatment:

Copper alloy single mating end all contact groupings

Gold single mating end single contact grouping and silver single mating end single contact grouping or silver single mating end single contact grouping

NSN 5935-01-087-9214Electrical Plug Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification all treatment responses
Included Contact Quantity:
3 single mating end 3rd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver or contact surfaces silver
Precious Material And Weight:
$0.051 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.051 \ \text{silver grains}, \ \text{troy} \ \text{or} \ 0.051 \ \text{silver grains}, \ \text{troy}$
0.051 gold grains, troy and 0.051 silver grains, troy or 0.051 silver grains, troy Precious Material:
Precious Material:
Precious Material: Gold and silver or silver
Precious Material: Gold and silver or silver Thread Series Designator:
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life:
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life: N/a
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life: N/a
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life: N/a Unit Of Measure:
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life: N/a Unit Of Measure: Demilitarization:
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life: N/a Unit Of Measure: Demilitarization: No
Precious Material: Gold and silver or silver Thread Series Designator: Uns and uns Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: