Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-088-2861

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.217 inches
Overall Height:
1.219 inches
Overall Width:
1.219 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
0.632 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
16-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

20

Thread Size:

0.938 inches

Terminal Location:

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## **Insert Material:**

Plastic epoxy single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

# Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and nickel

# **Included Contact Quantity:**

8 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

# Thread Series Designator:

Unef

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0