NSN 5935-01-088-5884

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-088-5884 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.766 inches **Overall Diameter:** 1.406 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-53 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.062 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Criticality Code Justification:** Feat

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-088-5884Electrical Plug Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy |
| Shell Surface Treatment: |
| Nickel |
| Shell Surface Treatment Specification: |
| Mil-c-26074 military specification single treatment response |
| Included Contact Quantity: |
| 53 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Pin no. 8 is wired to pin no. 28; mark item 3 m/t ecsgj1 |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.053 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-c-26074 spec. |