## NSN 5935-01-088-5886

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-088-5886 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.766 inches **Overall Diameter:** 1.406 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 18-53 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 30.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.062 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Criticality Code Justification:** Feat

**Terminal Type:** 

Crimp single mating end single contact grouping

## **NSN 5935-01-088-5886**Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Included Contact Quantity:
53 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Pin no. 8 is wired to pin no. 28; mark cap m/t ecsgj3
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.053 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26074 spec.