

View Online at <https://aerobasegroup.com/nsn/5935-01-088-6125>

**Thread Class:**

2b and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.330 inches

**Overall Diameter:**

0.840 inches

**Environmental Protection:**

Shock proof and vibration proof

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd 2nd mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Frequency Rating:**

18000.0 megahertz all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling ring and externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thready Qty Per Inch (tpi):**

24 and 36

**Thread Size:**

0.625 inches and 0.250 inches

**Shell Material:**

Steel

**Included Contact Quantity:**

1 2nd mating end single contact grouping

**Included Contact Type:**

Coaxial socket 2nd mating end single contact grouping

**Thread Series Designator:**

Unef and uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0