

View Online at <https://aerobasegroup.com/nsn/5935-01-088-6127>

Thread Class:

2b and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.380 inches

Overall Diameter:

0.840 inches

Environmental Protection:

Shock proof and vibration proof

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Nonstd 2nd mating end

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Frequency Rating:

18000.0 megahertz all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

Thready Qty Per Inch (tpi):

24 and 36

Thread Size:

0.625 inches and 0.250 inches

Shell Material:

Steel

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial pin all mating ends all contact groupings

Thread Series Designator:

Unef and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0