

View Online at <https://aerobasegroup.com/nsn/5935-01-088-6132>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

1.560 inches

**Overall Height:**

1.237 inches

**Overall Width:**

0.532 inches

**Environmental Protection:**

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

**Threaded Device Type:**

Coupling facility and mounting stud

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20 20-20 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Jackscrew-socket

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, gr c military specification single treatment response single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Zinc

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

9 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Keying plug position b and keying socket position u unfilled

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.009 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.