NSN 5935-01-088-6133

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-088-6133

Body Style:
Straight shape
Overall Length:
3.125 inches
Overall Height:
0.671 inches
Overall Width:
0.500 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.152 inches
Distance Between Mounting Facility Centers:
2.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty gdi-30 military specification single material response single mating end

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

NSN 5935-01-088-6133

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.