## NSN 5935-01-088-8253

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-088-8253 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.200 inches **Distance From Mounting Shoulder To Front Face:** 0.830 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Silver

**Included Contact Quantity:** 

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round w/flat

## NSN 5935-01-088-8253

Electrical Receptacle Connector - Page 2 of 2



Inc	luded	d Con	tact	Type:
	IUUC	4 <b>O</b> OH	ıavı	IVDC.

Coaxial pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold and shell surface silver

**Precious Material And Weight:** 

0.005 gold grains, troy and 0.100 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0