

View Online at <https://aerobasegroup.com/nsn/5935-01-089-0669>

**Thread Class:**

2a and 2a

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.590 inches

**Overall Diameter:**

0.562 inches

**Distance From Mounting Shoulder To Front Face:**

0.418 inches

**Threaded Device Type:**

Coupling facility and mounting bushing

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Nonstd all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

36 and 28

**Thread Size:**

0.190 inches and 0.438 inches

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Rubber all mating ends

**Contact Material Specification:**

Mil-e-13282 military specification single material response all mating ends single contact grouping

**Shell Material:**

Copper alloy

**Shell Material Specification:**

Qq-b-626 federal specification single material response

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Bushing Accommodation Hole Shape:**

Round

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Precious Material And Weight:**

0.010 gold grains, troy and 0.200 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Uns and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-e-13282 spec.