Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-089-2134

## **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.000 inches **Overall Diameter:** 1.250 inches **Environmental Protection:** Waterproof **Threaded Device Type:** Back shell and coupling facility Mating End Quantity: 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 and 9 **Thread Size:** 0.750 inches and 1.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Rubber synthetic single mating end Shell Material: Steel **Shell Surface Treatment:** Passivate



**Included Contact Quantity:** 

6 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## Thread Series Designator:

Unf and special acme

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0