

View Online at <https://aerobasegroup.com/nsn/5935-01-089-3767>

**Body Style:**

Pcb, angle shape, external coupling

**Overall Length:**

1.047 inches

**Overall Height:**

0.594 inches

**Overall Width:**

0.375 inches

**Environmental Protection:**

Corrosion resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 single mating end all contact groupings

**Contact Maximum Frequency Rating:**

12400.0 megahertz single mating end all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end all contact groupings

**Terminal Location:**

Side single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Insert Material:**

Plastic fluorocarbon single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings

**Terminal Type:**

Pin single mating end all contact groupings

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end 1st contact grouping

**Shell Material:**

Copper alloy 360

**Shell Surface Treatment:**

Gold

**Shell Material Specification:**

Qq-b-626 federal specification single material response

**Insert Material Specification:**

L-p-403 federal specification single material response single mating end

**Included Contact Quantity:**

1 single mating end 2nd contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.110 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.