NSN 5935-01-089-5145

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-089-5145 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 0.766 inches **Overall Diameter:** 1.531 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 20-39 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.188 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Terminal Type:** Crimp single mating end all contact groupings **Shell Material:**

Aluminum alloy

NSN 5935-01-089-5145

Mil-c-38999 spec.

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
37 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.039 gold grains, troy and 0.039 silver grains, troy
Precious Material:
Gold and silver
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27484 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):