

View Online at <https://aerobasegroup.com/nsn/5935-01-089-5151>

**Body Style:**

Straight shape, rectangular

**Overall Length:**

6.220 inches

**Overall Width:**

0.366 inches

**Unthreaded Mounting Hole Diameter:**

0.068 inches

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

3.0 single mating end all contact groupings

**Polarization Method:**

Guide pin/socket

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Nickel single mating end all contact groupings and gold single mating end all contact groupings

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Qq-n-290 cl 2 federal specification 1st treatment response single mating end all contact groupings and mil-g-45204 ty ii, grade c, cl 1 military specification 2nd treatment response single mating end all contact groupings

**Terminal Type:**

Pin single mating end all contact groupings

**Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end all contact groupings or qq-c-530 federal specification single material response single mating end all contact groupings

**Insert Material Specification:**

Mil-m-14 ty sdg-f military specification single material response single mating end or mil-p-19833 ty gdi-30f military specification single material response single mating end

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

49 single mating end 1st contact grouping

**Included Contact Type:**

Round socket single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.160 gold grains - tray

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.