# NSN 5935-01-089-6686

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-089-6686

## **Body Style:**

Straight shape, external coupling w/backshell

**Overall Length:** 

1.328 inches

**Overall Height:** 

1.141 inches

**Overall Width:** 

1.141 inches

**Environmental Protection:** 

Moisture proof

Mating End Quantity:

1

## **Contact Position Arrangement Style:**

12 single mating end

Contact Removability:

## Removable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

## **Polarization Method:**

Key, multiple key groove

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

**Connector Locking Method:** 

Bayonet pin

**Terminal Location:** 

Back single mating end single contact grouping

#### **Contact Material:**

Copper single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Insert Material:**

Rubber single mating end

### **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# NSN 5935-01-089-6686

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Anodize

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0