Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-089-8783

## Body Style:

Straight type

**Overall Length:** 

3.900 inches

## **Overall Height:**

0.545 inches

## **Overall Width:**

0.400 inches

#### **Environmental Protection:**

Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof

## **Unthreaded Mounting Hole Diameter:**

0.120 inches

### Distance Between Mounting Facility Centers:

3.650 inches

### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

92 single mating end

### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Polarization Method:**

Guide pin/socket

#### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### Insert Material:

Plastic polyamide single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, cl 1, grade c military specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## **Guide Design And Location:**

D shape socket left-hand at 3 oclock

#### **Insert Material Specification:**

L-p-395 federal specification single material response single mating end

# Included Contact Quantity:

92 single mating end single contact grouping



Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.092 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.