NSN 5935-01-089-8784

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-089-8784

Inread Class:
2a and 2b and 2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.780 inches
Overall Height:
0.530 inches
Overall Width:
0.270 inches
Distance Between Mounting Facility Centers:
0.532 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
48 and 56
Thread Size:
0.099 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Glass single mating end and plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type gdi-30 military specification single material response single mating end

NSN 5935-01-089-8784

Electrical Receptacle Connector - Page 2 of 2



Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
11 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-male and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.011 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14 spec.