## NSN 5935-01-089-8788

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-089-8788

Body Style:
Right angle type
Overall Length:
3.900 inches
Overall Height:
0.500 inches
Overall Width:
0.509 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock proof and thermal shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.650 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
92 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
2 polarization posts
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
$Mil-g-45204, \ type \ 1, \ cl \ 1, \ grade \ c \ military \ specification \ single \ treatment \ response \ single \ mating \ end \ single \ contact \ grouping$
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Guide Design And Location:
Hexagon shape male post left-hand at 9 oclock and hexagon shape female post right-hand at 9 oclock
Insert Material Specification:

L-p-395 federal specification single material response single mating end

## **Included Contact Quantity:**

92 single mating end single contact grouping

## NSN 5935-01-089-8788

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.092 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.